



SUMITOMO

CARBIDE - CBN - DIAMOND

WDX SUMIDRILL

Promotion

90% Discount



■ Diameter

2D ø13.0mm to 55.0mm

3D ø13.0mm to 55.0mm

4D ø13.0mm to 55.0mm

(Part of the promotion)

Secure price advantage now!
15 Sept. 2026 - 28 Febr. 2027

Get a WDX SumiDrill body with
90% discount from one of our popular series.
Depending on Drilling Depth the maximum
qty. of inserts/set are 40 pcs.

**SUMITOMO
ELECTRIC
GROUP**



WDX TN E-164
Brochure

Order now and receive price advantage!

Select the required WDX SumiDrill body from our Tooling News, order the corresponding minimum order quantity of drilling inserts at the list price minus your customer discount and you will receive the WDX SumiDrill body with **90% discount**. List price in Euro plus VAT.

Minimum order quantity for cutting inserts:

→ **30pcs (for 2D/3D)**

→ **40pcs (for 4D)**

The promotion price is valid for the mentioned promotion period and only while stocks last.

Refer to the promotion "**WDX Promotion**" in your order. The promotion is valid from 15 September 2026 until 28 February 2027.


Remarks: 5D and Ø56 or larger are excluded from this promotion.

■ Insert

Dimensions (mm)


Application	Coated Carbide											
High-Speed / Light	P_k						N					
General Purpose	P	M_s	M									
Roughing	P					K						
Cat. No.	ACP100	ACP300	ACS3000	ACM300	ACK300	DL1500	Fig	W1	S	RE1	RE2	Applicable Holder
WDX T 042004 L	★	★			★		1					WDX130D5S20 – WDX150D5S20
042004 G	★	★			★	★	2	4.2	2.0	0.4	0.4	
042004 H	★	★			★		3					
042004 M			★	▲			4				0.8	
WDX T 052504 L	★	★			★		1					WDX155D5S20 – WDX180D5S25
052504 G	★	★			★	★	2	5.0	2.5	0.4	0.4	
052504 H	★	★			★		3					
052504 M			★	▲			4				1.0	
WDX T 063006 L	★	★			★		1					WDX185D5S25 – WDX225D5S25
063006 G	★	★			★	★	2	6.0	3.0	0.6	0.6	
063006 H	★	★			★		3					
063006 M			★	▲			4				1.4	
WDX T 073506 L	★	★			★		1					WDX230D5S25 – WDX280D5S32
073506 G	★	★			★	★	2	7.5	3.5	0.6	0.6	
073506 H	★	★			★		3					
073506 M			★	▲			4				1.6	
WDX T 094008 L	★	★			★		1					WDX290D5S32 – WDX360D5S40
094008 G	★	★			★	★	2	9.6	4.0	0.8	0.8	
094008 H	★	★			★		3					
094008 M			★	▲			4				2.4	
WDX T 125012 L	★	★			★		1					WDX370D5S40 – WDX450D5S40
125012 G	★	★			★	★	2	12.4	5.0	1.2	1.2	
125012 H	★	★			★		3					
125012 M			★	▲			4				3.2	
WDX T 156012 L	★	★			★		1					WDX460D5S40 – WDX550D5S40
156012 G	★	★			★	★	2	15.2	6.0	1.2	1.2	
156012 H	★	★			★		3					
WDX T 186012 L	★	★			★		1					WDX560D5S40 – WDX680D2S40
186012 G	★	★			★		2	18.0	6.0	1.2	1.2	
186012 H	★	★			★		3					

Fig. 1




For low feed with chip control

Fig. 2




General purpose

Fig. 3



Strong edge

Fig. 4



For stainless steel

★: Global stocked item
▲: To be replaced by a new product or discontinued (please confirm stock availability)